




Sandtex PVC



Sandtex is a matt clear embossed PVC overlaminating film exhibiting minimal glare and coated with a permanent acrylic adhesive suitable for overlamination of all ink types including UV inks. The rough textured light diffusing finish gives excellent anti-scuff and anti-slip properties and therefore this product is commonly used for floor graphics (industry tested and approved), pop-up displays and general paper and filmic poster graphic overlamination.

100 SAND-TEXTURED MATT PVC / PERM / 70 PE
KRAFT LINER (1 side Silicon)

Typical Available Widths:	880mm, 1040mm, 1300mm, 1530mm
Application Temperature:	+10°C - +40°C
Service Temperature:	-20°C - +70°C
Shelf Life:	1 year



Product Features and Performance Data

Component	Description	Details	Gauge (Microns)	Tolerance (Microns)
A	Matt clear PVC	Sand-textured, Monomerically plastisized.	100	+/- 10
B	Permenant adhesive	Exhibiting moderate tack and peel adhesion	30	+/- 2
C	White, Kraft, PE coated release liner	70 gsm, standard release, siliconised one side.	80	+/- 8

STORAGE: Effort must be made to keep this product free from moisture and excessive exposure to ultra violet radiation before use.

The data above does not constitute a guaranteed specification and is given in good faith. End users of this product are urged to test the product and the substrates concerned, in the specific application and exposure conditions in which the product will be utilised.